

### AMC-ANTGPGSPUCK-JA4M



- Quad Band GSM + GPS combination antenna
- GSM 850/900/1800/1900MHz
- GPS 1575.42MHz
- 77mm diameter x 14mm (H)
- Adhesive mounting
- Gain (typical):
  - GSM: 2dBi
  - GPS: 18dBi
- Cable (standard length)\*
  - 4m x RG-174
- Connectors (standard)\*
  - GSM – FME (F)
  - GPS – SMA (M)

### AMC-ANTGPSSM-A2M



- Sub-miniature GPS antenna
- 1575.42MHz
- 11.5mm x 11.5mm x 11.5mm
- Gain (typical): 22dB
- Cable (standard length)\*
  - 2m x RG-174
- Connector (standard)\*
  - GPS – SMA (M)

### AMC-ANTGPS088-JA4M



- Penta Band GSM + GPS combination antenna
- GSM 850/900/1800/1900MHz + 2.1GHz
- GPS 1575.42MHz
- 110mm (L) x 36mm (W) x 19mm (H)
- Adhesive mounting
- Gain (typical):
  - GSM: 2dBi
  - GPS: 18dBi
- Cable (standard length)\*
  - 4m x RG-174
- Connectors (standard)\*
  - GSM – FME (F)
  - GPS – SMA (M)

### AMC-ANTGSMBM2-J4M



- Waterproof (IP66) Penta Band GSM antenna
- GSM 850/900/1800/1900MHz + 2.1GHz
- 75mm diameter x 14mm (H)
- Body mounting
- Gain (typical): 2dBi
- Cable (standard length)\*
  - 4m x RG-174
- Connectors (standard)\*
  - GSM – FME (F)

### AMC-ANTGSMGPSBM2-JA4M



- Waterproof (IP66) Penta Band GSM + GPS combination antenna
- GSM 850/900/1800/1900MHz + 2.1GHz
- GPS 1575.42MHz
- 75mm diameter x 14mm (H)
- Body mounting
- Gain (typical):
  - GSM: 2dBi
  - GPS: 18dBi
- Cable (standard length)\*
  - 4m x RG-174
- Connectors (standard)\*
  - GSM – FME (F)
  - GPS – SMA (M)

### AMC-ANTGSMBM5-A5M



- Penta Band GSM antenna
- GSM 850/900/1800/1900MHz + 2.1GHz
- 76mm x 29mm (inc. foot)
- Body mounting
- Gain (typical): 2dBi
- Cable (standard length)\*
  - 5m x RG-58
- Connectors (standard)\*
  - GSM – SMA (M)

### AMC-ANTGPSMAG-A3M



- Waterproof (IP67) GPS antenna
- 1575.42MHz
- 54mm x 44mm x 15mm
- Magnetic mounting
- Gain (typical): 27dB
- Cable (standard length)\*
  - 3m x RG-174
- Connector (standard)\*
  - GPS – SMA (M)

### AMC-CELLSTRIPO1-J2.5M



- Waterproof (IP67) Penta Band GSM antenna
- GSM 850/900/1800/1900MHz + 2.1GHz
- 131mm x 12mm x 4mm
- Adhesive mounting
- Gain (typical): 2dBi
- Cable (standard length)\*
  - 2.5m x RG-174
- Connector (standard)\*
  - GSM – FME (F)

\*Cable length and connector type can be customised on request

All specifications are correct at time of printing