



Specification:

- * Withstanding Voltage: 500V DC /1M.
- * Insulation Resistance: 1000M Ohm
- * Voltage Rating: 5V AC
- * Current Rating: 0.5A/Product Max.
- * Contact Resistance: 60m Ohm Max.
- * Operating Temperature: -25°C ~ +85°C
- * Insertion Cycles: 10000 Times Min
- * Press Force: 0.2N~0.6N

Material and Finish:

- * Housing: LCP+30%G.F. UL 94V-0, Black
- * Contact: Copper Alloy
- * Contact Area: Gold Plating All Over Ni

ORDER INFORMATION:

SIMMP-P XX XX BT X 0

- NO. OF CONTACTS:
 - 06: 6PIN
 - 08: 8PIN
- Packing:
 - O: Tube
 - R: Tape & Reel
- Plating:
 - 10: 10u"
 - 30: 30u"

DIMENSION IN mm [inch]		PROD. SPEC.
TOLERANCE UNLESS OTHERWISE SPECIFIED		PRG. SPEC.
.X±0.30	X.±	APPROVE
.XX±0.20	.X.±	CHECK
.XXX±0.10	.XX.±	DRAW
AMC--ICA-581 SIM CARD holder		
TITLE SIM CARD CONN. PUSH-IN/OUT		CUSTOMER DRAWING
FILE NO. SIM-KF016		
DWG NO. SIMMP-PXXXXBTX0		
SIZE A4	PROL. SHEET 1	
SCALE 2:1	REV B	

REV	MODIFICATION	DATE	DRAW
B	EN-06-1125	95/11/27	TERENCE