



GSA-8821

“I Bar” Telematic GSM Antenna

(GSM / CDMA / PCS / DCS / UMTS/ WCDMA)



Top View



Side View

The **I Bar** is flexible and robust for fast installation. It is designed for covert and convenient use in the telematics industry. It is ideal for tracking systems.

The antenna has been subject to rigorous IP67 waterproof testing and can handle full immersion in water for extended periods of time.

Features

Cellular

- Penta-band GSM (GSM / CDMA / PCS / DCS / UMTS/ WCDMA)
- Worldwide use
- Constant reception and transmission – due to omni directional gain across all bands
- Optional cables and connectors (RG-174, SMA(M), FME(M), FME(F), MCX(M), etc.)
- Waterproof to IP67
- ROHS Compliant
- Achieves a permanent and secure fix by using 3m double sided tape

Authorised Distributor: Alpha Micro Components Ltd | Tel: +44 1256 851770 | e: sales@alphamicro.net | www.alphamicro.net



Specifications

ELECTRICAL					
	AMPS	GSM	DCS	PCS	UMTS
Band	824-896	880-960	1710-1880	1850-1990	1710- 2170
Average Gain	3dBi				
Polarization	Linear				
Impedance	50 ohms				
Input Power	10 watts				
Input Connection	Coaxial Cable - RG174 Standard, Fully customizable				
VSWR (Min performance)	<2.0:1				
MECHANICAL					
Dimensions (L x W x H)	Length 105mm x Width 14mm x Height 3mm				
Weight	40g				
Casing	UV Resistant TPE				
Waterproofing	Sealing Film				
ENVIRONMENTAL					
Waterproof	IP-67 - No internal water entry				
	after 30mins immersion in 1M water				
Temperature Range	-40°C to +85°C				
Thermal Shock	100 cycles -40°C to +80°C				
Humidity	Non-condensing 65°C 95% RH				
Shock (Drop Test)	1m drop on concrete 6 axes				
Cable Pull	8 KGf				

Authorised Distributor: Alpha Micro Components Ltd | Tel: +44 1256 851770 | e: sales@alphamicro.net | www.alphamicro.net