

# LEA-5T

## u-blox 5 GPS receiver with Precision Timing

### Product description

The LEA-5T supports precision GPS timing for demanding positioning applications such as femto cells and WiMAX base-stations. It features a time mode function whereby the GPS receiver assumes a stationary 3D position, whether programmed manually or determined by an initial self-survey. Stationary operation enables GPS timing with only one visible satellite and eliminates timing errors which otherwise result in positioning errors. An accuracy of up to 15 ns is achievable by using the quantization error information to compensate the granularity of the time pulse. A built-in time mark and counter unit provide precise time measurement of external event inputs.



22.4 x 17 x 3 mm

### Highlights

- 50-channel u-blox5 engine with over 1 million effective correlators
- < 1 second Time-To-First-Fix for hot and aided starts
- SuperSense® indoor GPS with best-in-class acquisition and tracking sensitivity
- Supports AssistNow Online A-GPS service; OMA SUPL compliant
- Hybrid GPS, GALILEO and SBAS (WAAS, EGNOS, MSAS, GAGAN) engine
- Stationary mode for GPS timing operation
- Output timepulse with at least one satellite in view

### Features

Series	Power	Size	Memory	Function	Antenna	Input / Output
	Voltage range [V]	Thickness [mm]	Programmable (Flash) FW update	Power Save mode KickStart Dead Reckoning Raw data Precision Timing	Antenna supply Antenna supervisor	UART USB SPI DDC (I <sup>2</sup> C compliant) Reset input Configuration pin
LEA-5T	2.7 - 3.6	3		P • • •	• •	1 1 1 •

P = Planned

## Mechanical data



Dimensions  
22.4 x 17 x 3 mm

Weight  
2.1 g

## Electrical data

Power supply	2.7 to 3.6 V
Power consumption	126 mW @ 3.0 V Eco mode 141 mW @ 3.0 V Max. performance mode
Backup power	1.4 V to 3.6 V, 25 $\mu$ A
Antenna type	Active and passive
Antenna power	External or internal VCC_RF
Antenna supervision	Integrated short-circuit detection and antenna shutdown, open circuit detection is supported with AADET_N input and little external circuitry

## Timer performance data

Timing accuracy	RMS	30 ns
	99%	< 60 ns
	Granularity	21 ns
	Compensated	15 ns <sup>1</sup>
Time pulse	Configurable	0.25 to 1000 Hz
Time mark / Counter	# of Inputs	1

<sup>1</sup> Quantization error information can be used to compensate the granularity related error of the time pulse signal

## Ordering information

LEA-5T-0 u-blox 5 Precision Timing GPS Module

Available as samples and tape on reel (250 pieces)

### Legal Notice

u-blox reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. Reproduction, use, modification or disclosure to third parties of this document or any part thereof without the express permission of u-blox is strictly prohibited.

The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit [www.u-blox.com](http://www.u-blox.com).

Copyright © 2009, u-blox AG

## Interfaces

Serial interfaces	1 UART 1 USB V2.0 full speed 12 Mbit/s 1 DDC (I <sup>2</sup> C compliant)
Digital I/O	Configurable time pulse 1 EXTINT input 1 reset
Serial and I/O voltages	2.7 to 3.6 V
Protocols	NMEA, UBX binary

## Receiver performance data

Receiver type	50-channel u-blox5 engine GPS L1 C/A code SBAS: WAAS, EGNOS, MSAS, GAGAN	
Accuracy <sup>2</sup>	Position	2.5 m CEP
	SBAS	2.0 m CEP
Acquisition <sup>2</sup>	Cold starts:	29 s
	Warm starts:	29 s
	Aided starts <sup>3</sup> :	< 1 s
	Hot starts:	< 1 s
Sensitivity <sup>4</sup>	Cold starts:	-144 dBm
	Reacquisition:	-160 dBm
	Tracking:	-160 dBm
Multipath suppression	Intelligent multipath detection and suppression	
A-GPS	Supports AssistNow Online and AssistNow Offline, OMA SUPL compliant	
Operational limits	Velocity:	500 m/s (972 knots)
	Altitude:	50,000 m
Operating temp.	-40° C to 85° C	
Storage temp.	-40° C to 85° C	

<sup>2</sup> All SV @ -130 dBm

<sup>3</sup> Dependent on aiding data connection speed and latency

<sup>4</sup> Demonstrated with a good active antenna

## Support products

EVK-5T u-blox 5 Evaluation Kit with Precision Timing

## Contact us

HQ Switzerland  
+41 44 722 7444  
[info@u-blox.com](mailto:info@u-blox.com)

China  
+86 10 68 133 545  
[info\\_cn@u-blox.com](mailto:info_cn@u-blox.com)

EMEA  
+41 44 722 7444  
[info@u-blox.com](mailto:info@u-blox.com)

Japan  
+81 3 5775 3850  
[info\\_jp@u-blox.com](mailto:info_jp@u-blox.com)

Americas  
+1 703 483 3180  
[info\\_us@u-blox.com](mailto:info_us@u-blox.com)

Korea  
+82 02 542 0861  
[info\\_kr@u-blox.com](mailto:info_kr@u-blox.com)

APAC – Singapore  
+65 6734 3811  
[info\\_ap@u-blox.com](mailto:info_ap@u-blox.com)

Taiwan  
+886 2 2657 1090  
[info\\_tw@u-blox.com](mailto:info_tw@u-blox.com)